

SAFETY DATA SHEET

A97W1251

Section 1. Identification

Product name : DURATION HOME® Interior Latex Satin
Coating Extra White

Product code : A97W1251

Other means of identification : Not available.

Product type :

Liquid.

Relevant identified uses of the substance or mixture and uses advised against
Paint or paint related material.

Manufacturer : THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue
Cleveland, OH 44115

:
US / Canada: (800) 424-9300

Emergency telephone number of the company : hours and 365 days a year
Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24

Product Information Telephone Number : US / Canada: 1-800-474-3794
Mexico: Not Available

Regulatory Information Telephone Number : US / Canada: (216) 566-2902
Mexico: Not Available

Transportation Emergency : US / Canada: (800) 424-9300

Telephone Number : hours and 365 days a year
Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture :
CARCINOGENICITY - Category 1A TOXIC
TO REPRODUCTION - Category 2

GHS label elements

Hazard pictograms :

Signal word : Danger

Hazard statements :

May cause cancer.
Suspected of damaging fertility or the unborn child.

General : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection.

Date of issue/Date of revision : 9/14/2023 *Date of previous issue :* 6/10/2023 *Version :* 25 1/14A97W1251 DURATION HOME® Interior Latex Satin Coating

Extra White

SHW-85-NA-GHS-US

Section 2. Hazards identification

Response : IF exposed or concerned: Get medical advice or attention. **Storage :** Store locked up.

Disposal Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements

sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure. Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.

Hazards not otherwise classified

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Adequate ventilation required when

: None known.

Section 3. Composition/information on ingredients

Substance/mixture :
Other means of identification Mixture : Not available.

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Titanium Dioxide	≥10 - ≤25 ≤3	13463-67-7
Vinyl Chloride Polymer	<1	9002-86-2
Crystalline Silica, respirable powder	≤0.3	14808-60-7
2-Ethyl-2-(hydroxymethyl)-1,3-propanediol	≤0.3	77-99-6
Cristobalite, respirable powder		14464-46-1

Any concentration shown as a range is to protect confidentiality or is due to batch variation. **There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.**

Section 4. First aid measures

Description of necessary first aid measures

Eye contact Inhalation

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Date of Issue/Date of revision : 9/14/2023 Date of previous issue : 6/10/2023 Version : 25 2/14A97W1251 DURATION HOME® Interior Latex Satin Coating

SHW-85-NA-GHS-US

Extra White

Section 4. First aid measures

Ingestion :

Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : No known significant effects or critical hazards.

Skin contact : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation Adverse symptoms may include the following:

:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Skin contact Ingestion : : Adverse symptoms may include the following: reduced fetal weight	increase in fetal deaths skeletal malformations : Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
---	---

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media :	Use an extinguishing agent suitable for the surrounding fire.
--	---

Unsuitable extinguishing media :	None known.
--	-------------

In a fire or if heated, a pressure increase will occur and the container may burst.

Specific hazards arising from the chemical
:

Date of Issue/Date of revision : 9/14/2023 Date of previous issue : 6/10/2023 Version : 25 3/14A97W1251 DURATION HOME® Interior Latex Satin Coating

Coating

Extra White

SHW-85-NA-GHS-US

Section 5. Fire-fighting measures

Hazardous thermal decomposition products :	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides halogenated compounds metal oxide/oxides
--	---

Special protective actions

: Immediately isolate the scene by removing all persons from the vicinity of the incident if

for fire-fighters **Special protective**

there is a fire, No action shall be taken involving any personal risk or without suitable training.

:
equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do

not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non emergency personnel".

Environmental precautions

:

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill :

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill :

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures Put on appropriate personal protective equipment (see Section 8). Avoid exposure -

:

obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Section 7. Handling and storage

Advice on general

Eating, drinking and smoking should be prohibited in areas where this material is

occupational hygiene Conditions for safe storage,

handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

including any

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
-----------------	-------	-----------------

Titanium Dioxide 13463-67-7 **OSHA PEL (United States, 5/2018).** TWA: 15 mg/m³ 8 hours. Form: Total dust
ACGIH TLV (United States, 1/2023).
TWA: 2.5 mg/m³ 8 hours. Form: respirable fraction, finescale particles

Vinyl Chloride Polymer 9002-86-2 **ACGIH TLV (United States, 1/2023).** TWA: 1 mg/m³ 8 hours. Form: Respirable fraction

Crystalline Silica, respirable powder 14808-60-7 **OSHA PEL Z3 (United States, 6/2016).** TWA: 250 mppcf / (%SiO₂+5) 8 hours. Form:
Respirable
TWA: 10 mg/m³ / (%SiO₂+2) 8 hours. Form: Respirable
OSHA PEL (United States, 5/2018). [Silica, crystalline]
TWA: 50 µg/m³ 8 hours. Form: Respirable dust
ACGIH TLV (United States, 1/2023). [Silica, crystalline]
TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction
NIOSH REL (United States, 10/2020). [SILICA, CRYSTALLINE (AS RESPIRABLE DUST)]
TWA: 0.05 mg/m³ 10 hours. Form: respirable dust

2-Ethyl-2-(hydroxyméthyl)-1,3-propanediol 77-99-6 None.
Cristobalite, respirable powder 14464-46-1 **OSHA PEL Z3 (United States, 6/2016).** TWA: 250 mppcf / 2 x (%SiO2+5) 8 hours.
Form: Respirable
TWA: 10 mg/m³ / 2 x (%SiO2+2) 8 hours.
Form: Respirable
TWA: 30 mg/m³ / 2 x (%SiO2+2) 8 hours.
Form: Total dust
OSHA PEL (United States, 5/2018). [Silica, crystalline]
TWA: 50 µg/m³ 8 hours. Form: Respirable

Date of issue/Date of revision : 9/14/2023 Date of previous issue : 6/10/2023 Version : 25 5/14A97W1251 DURATION HOME® Interior Latex Satin Coating
Extra White
SHW-85-NA-GHS-US

Section 8. Exposure controls/personal protection

		dust ACGIH TLV (United States, 1/2023). [Silica,crystalline] TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction NIOSH REL (United States, 10/2020). [SILICA, CRYSTALLINE (AS RESPIRABLE DUST)] TWA: 0.05 mg/m³ 10 hours. Form: respirable dust
--	--	---

Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
-----------------	-------	-----------------

Quartz	14808-60-7	CA British Columbia Provincial (Canada,6/2022). [Silica, Crystalline - alpha quartz and Cristobalite Respirable] TWA: 0.025 mg/m³ 8 hours. Form: Respirable CA Quebec Provincial (Canada, 6/2022). [Silica Crystalline -Quartz] TWA: 0.1 mg/m³ 8 hours. Form: Respirable dust. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 0.025 mg/m³ 8 hours. Form: Respirable particulate CA Ontario Provincial (Canada, 6/2019). [Silica, Crystalline (Quartz/Tripoli)] TWA: 0.1 mg/m³ 8 hours. Form: Respirable particulate matter. CA Saskatchewan Provincial (Canada, 7/2013). TWA: 0.05 mg/m³ 8 hours. Form: respirable fraction
Cristobalite	14464-46-1	CA British Columbia Provincial (Canada,6/2022). [Silica, Crystalline - alpha quartz and Cristobalite Respirable] TWA: 0.025 mg/m³ 8 hours. Form: Respirable CA Quebec Provincial (Canada, 6/2022). TWA: 0.05 mg/m³ 8 hours. Form: Respirable dust. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 0.025 mg/m³ 8 hours. Form: Respirable particulate CA Ontario Provincial (Canada, 6/2019). TWA: 0.05 mg/m³ 8 hours. Form: Respirable particulate matter. CA Saskatchewan Provincial (Canada, 7/2013). TWA: 0.05 mg/m³ 8 hours. Form: respirable fraction

Occupational exposure limits (Mexico)

	CAS #	Exposure limits
None.		

Date of issue/*Date of revision* : 9/14/2023 *Date of previous issue* : 6/10/2023 *Version* : 25 6/14A97W1251 DURATION HOME® Interior Latex Satin Coating

Extra White

SHW-85-NA-GHS-US

Section 8. Exposure controls/personal protection**Biological exposure indices (United States)**

No exposure indices known.

Biological exposure indices (Canada)

No exposure indices known.

Biological exposure indices (Mexico)

No exposure indices known.

Appropriate engineering controls**Environmental exposure controls**

: If user operations generate dust, fumes, gas, vapor or mist.

use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases fume

scrubbers, filters or engineering modifications to the process acceptable levels.
equipment will be necessary to reduce emissions to

Individual protection measures

Hygiene measures :
Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.
Appropriate techniques should be used to remove potentially contaminated clothing.
Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Skin protection Hand protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side shields.

Body protection Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection :
Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state Liquid. :

Color Not available. :

Odor Not available. :

Date of issue/Date of revision : 9/14/2023 Date of previous issue : 6/10/2023 Version : 25 7/14A97W1251 DURATION HOME® Interior Latex Satin Coating

SHW-85-NA-GHS-US

Extra White

Section 9. Physical and chemical properties

Odor threshold Not available.

pH : 9

Melting point/freezing point : Not available.

Boiling point, initial boiling : 100°C (212°F)

point, and boiling range : Closed cup: Not applicable.

Flash point

Evaporation rate 0.09 (butyl acetate = 1) :

Flammability : Not available.

Lower and upper explosion : Not available.

limit/flammability limit

Vapor pressure 2.3 kPa (17.5 mm Hg)

Relative vapor density : 1 [Air = 1]

Relative density 1.26

Solubility(ies) :

Media	Result
cold water	Partially soluble.

Partition coefficient: n :
octanol/water Not applicable.

Auto-ignition temperature :
Not available.

Decomposition temperature : Not available.

Viscosity Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)

Molecular weight : Not applicable.

Heat of combustion : 0.816 kJ/g

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid No specific data.

Incompatible materials :

No specific data.

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-Ethyl-2-(hydroxymethyl)-1,3-propanediol	LD50 Oral	Rat	14000 mg/kg	-

Date of issue/Date of revision : 9/14/2023 Date of previous issue : 6/10/2023 Version : 25 8/14A97W1251 DURATION HOME® Interior Latex Satin Coating

SHW-85-NA-GHS-US

Extra White

Section 11. Toxicological information

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Product/ingredient name	OS HA	IARC	NTP
Titanium Dioxide Vinyl Chloride Polymer	-	2B	-
Crystalline Silica, respirable powder	-	3	-
	+	1	Known to be a human carcinogen.
Cristobalite, respirable powder	+	1	Known to be a human carcinogen.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Crystalline Silica, respirable powder	Category 1	inhalation	-
Cristobalite, respirable powder	Category 1	inhalation	respiratory tract

Aspiration hazard

Not available.

Information on the likely

: Not available.

routes of exposure

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : No known significant effects or critical hazards.

Skin contact : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Date of issue/Date of revision : 9/14/2023 Date of previous issue : 6/10/2023 Version : 25 9/14A97W1251 DURATION HOME® Interior Latex Satin Coating

Extra White

SHW-85-NA-GHS-US

Section 11. Toxicological information

Inhalation Adverse symptoms may include the following:

:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Skin contact Ingestion

increase in fetal deaths
skeletal malformations

:
Adverse symptoms may include the following: reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available. Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.

Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of exposure. **Mutagenicity** :

No known significant effects or critical hazards.

Teratogenicity : Suspected of damaging the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : Suspected of damaging fertility.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium Dioxide 2-Ethyl-2-(hydroxymethyl)-1,3-propanediol	Acute LC50 >1000000 µg/l Marine water	Fish - <i>Fundulus heteroclitus</i>	96 hours
	Acute EC50 13000000 µg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 14400000 µg/l Marine water	Fish - <i>Cyprinodon variegatus</i>	96 hours

Persistence and degradability

Not available.

Date of issue/Date of revision : 9/14/2023 Date of previous issue : 6/10/2023 Version : 25 10/14A97W1251 DURATION HOME® Interior Latex Satin Coating

SHW-85-NA-GHS-US

Extra White

Section 12. Ecological information

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
2-Ethyl-2-(hydroxymethyl)-1,3-propanediol	-	<1	Low

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Disposal methods :

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all time comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable product via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of a authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

waterways, drains
and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification
UN number	Not regulated.	Not regulated.
UN proper shipping name	-	-
Transport hazard class(es)	-	-
Packing group	-	-

Environment al hazards	No.	No.
Additional information	-	-

Date of issue/Date of revision : 9/14/2023 Date of previous issue : 6/10
Coating

Extra White

Section 14. Transport information

Special precautions for user

: Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according

:
Not available.

to IMO instruments

Proper shipping name :

Not available.

Section 15. Regulatory information

TSCA 5(a)2 proposed significant new use rules: 2-Methyl-4-isothiazolin-3-one;
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and
2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations

Montreal Protocol

Not listed.

Not listed.

International lists :

Australia inventory (AIIC): Not determined.
China inventory (IECSC): Not determined.
Japan inventory (CSCL): Not determined.
Japan inventory (ISHL): Not determined.
Korea inventory (KECI): Not determined.
New Zealand Inventory of Chemicals (NZIoC): Not determined.
Philippines inventory (PICCS): Not determined.
Taiwan Chemical Substances Inventory (TCSI): Not determined.
Thailand inventory: Not determined.
Turkey inventory: Not determined.
Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

	*		0
			0
			0

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Date of issue/Date of revision : 9/14/2023 Date of previous issue : 6/10/2023 Version : 25 12/14A97W1251 DURATION HOME® Interior Latex Satin Coating

SHW-85-NA-GHS-US

Extra White

Section 16. Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification

Justification

CARCINOGENICITY - Category 1A
TOXIC TO REPRODUCTION - Category 2

Calculation method
Calculation method

History

Date of printing :
Date of issue/Date of revision : 9/14/2023 :
9/14/2023

Date of previous issue :
6/10/2023

Version : 25

Key to abbreviations :

ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973
as modified by the Protocol of 1978. ("Marpol" = marine pollution)
N/A = Not available
SGG = Segregation Group
UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

Date of issue/Date of revision : 9/14/2023 Date of previous issue : 6/10/2023 Version : 25 13/14A97W1251 DURATION HOME® Interior Latex
Satin Coating

SHW-85-NA-GHS-US

Extra White

Date of issue/Date of revision : 9/14/2023 Date of previous issue : 6/10/2023 Version : 25 14/14A97W1251 DURATION HOME® Interior Latex
Satin Coating

SHW-85-NA-GHS-US

Extra White