SAFETY DATA SHEET

1. Identification

Product number

1000000962

Product identifier

MULTI-PURPOSE ANTI-STATIC SPRAY

Company information

Claire Manufacturing Co.

1005 S. Westgate Drive Addison, IL 60101 United States

Company phone

General Assistance 1-630-543-7600

Emergency telephone US Emergency telephone outside 1-866-836-8855

US

1-952-852-4646

Version #

01

Recommended use

Antistatic agent

Recommended restrictions

None known.

2. Hazard(s) identification

Physical hazards

Flammable aerosols

Category 1

Health hazards

Serious eye damage/eye irritation

Category 2

Environmental hazards

Not classified.

OSHA defined hazards

Not classified.

Label elements





Signal word

Hazard statement

Extremely flammable aerosol. Causes serious eye irritation.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Wash thoroughly after handling. Wear eye/face protection.

Response

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If eye

irritation persists: Get medical advice/attention.

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

Not available.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	% 60 - 80	
Ethyl Alcohol		64-17-5		
1,1-Difluoroethane		75-37-6	20 - 40	
Other components below reportable levels			0.1 - 1	

^{#:} This substance has workplace exposure limit(s).

Product name: MULTI-PURPOSE ANTI-STATIC SPRAY

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician if symptoms develop or persist.

Skin contact

For minor skin contact, avoid spreading material on unaffected skin.

Eve contact

Rinse with water.

Ingestion

If material is ingested, immediately contact a poison control center. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. No need for first aid is anticipated if material is swallowed.

Most important symptoms/effects, acute and delayed

Headache. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Skin irritation.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm, Keep victim under observation. Symptoms may be delayed.

General information

In case of shortness of breath, give oxygen. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Keep victim under observation. Keep victim warm.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from

the chemical Special protective equipment

and precautions for firefighters Fire-fighting

equipment/instructions

Specific methods

General fire hazards

Personal precautions. protective equipment and emergency procedures

6. Accidental release measures

Methods and materials for containment and cleaning up

Environmental precautions

Powder, Alcohol resistant foam, Carbon dioxide (CO2).

Do not use a solid water stream as it may scatter and spread fire.

Contents under pressure, Pressurized container may explode when exposed to heat or flame.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Movecontainers from fire area if you can do so without risk. Use water spray to cool unopened

containers. In the event of fire and/or explosion do not breathe fumes.

Extremely flammable aerosol.

Keep unnecessary personnel away, Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages

cannot be contained. For personal protection, see section 8 of the SDS. Refer to attached safety data sheets and/or instructions for use. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil,

etc.) away from spilled material. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Keep out of low areas. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. If possible, turn leaking containers so that gas escapes rather than liquid. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. After removal flush contaminated area thoroughly with water. This material and its container must be disposed of as hazardous waste.

Avoid discharge into drains, water courses or onto the ground.

Productiname: MULTI-PURPOSE ANTI-STATIC SPRAY

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing dust/fume/gas/mist/vapors/spray, Avoid contact with skin, Avoid contact with eyes, Avoid prolonged exposure. Use only in area provided with appropriate exhaust ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Handle and open container with care. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Keep away from heat, sparks, and flame, Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. The pressure in sealed containers can increase under the influence of heat, Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source, Store in a well-ventilated place. Refrigeration recommended. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). Level 2 Aerosol.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air	Contaminants (29 CFR 1910.1000)
On minimum and a	₹

Components	Type	value	
Ethyl Alcohol (CAS 64-17-5)	PEL	1900 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit Values	i		
Components	Туре	Value	
Ethyl Alcohol (CAS 64-17-5)	STEL	1000 ppm	
US, NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	
Ethyl Alcohol (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	
US. Workplace Environmental Exp	osure Level (WEEL) Guides		
Components	Туре	Value	
1,1-Difluoroethane (CAS	TWA	2700 mg/m3	
75-37-6)		1000 ppm	
		ταοά bhui	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide evewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Hand protection

Wear appropriate chemical resistant gloves.

Skin protection

Other

Wear suitable protective clothing.

No Exposure standards allocated.

Respiratory protection

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary...

General hygiene considerations

Do not get in eyes. When using do not smoke. Avoid contact with skin, Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Product name: MULTI-PURPOSE ANTI-STATIC SPRAY

9. Physical and chemical properties

Appearance

Physical state

Gas.

Form

Aerosol.

Color

clear colorless

Odor

Characteristic.

Odor threshold

Not available.

рΗ

Not applicable estimated

Melting point/freezing point

Not available.

initial boiling point and boiling

134.9 °F (57.17 °C) estimated

галде

Flash point

-58.0 °F (-50.0 °C) Propellant estimated

Evaporation rate

Not available.

Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits

Flammability Ilmit - lower

2.6 % estimated

(%)

Flammability limit - upper

12.8 % estimated

(%)

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

27 - 37 psig @70F estimated

Vapor density

Not available.

Relative density

Not available.

Solubility(ies)

Solubility (water)

Not available.

Partition coefficient

(n-octanol/water)

Not available.

Auto-ignition temperature

856.4 °F (458 °C) estimated

Decomposition temperature Viscosity Not available. Not available.

Other information

Specific gravity

0.812 estimated

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Risk of ignition.

Possibility of hazardous

Hazardous polymerization does not occur.

reactions

Conditions to avoid

Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible

materials.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition

No hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Ingestion

Not ävailable.

Inhalation

Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Causes serious eye irritation,

Product name: MULTI-PURPOSE ANTI-STATIC SPRAY

Symptoms related to the physical, chemical and toxicological characteristics

Headache. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging.

tearing, redness, swelling, and blurred vision. Coughing. Skin irritation.

Information on toxicological effects

Acute toxicity

Acute LC50: 157 mg/l/4h, Rat, Inhalation

Acute toxicity	Species Test Results		
Product			
MULTI-PURPOSE ANTI-STATI	IC SPRAY (CAS Mixture)		
Acute Dermal			
LD50	Rat		
Inhalation			
LC50	Rat	157 mg/l/4h	
Oral			
LD50	Rat		
Components	Species	Test Results	
1,1-Difluoroethane (CAS 75-37	-6)		
Acute			
Inhalation	677	i	
LC50	Rat	44 - 437500 %, 4 Hours	
Ethyl Alcohol (CAS 64-17-5)			
Acute Inhalation			
LC50	Cat	85.41 mg/l _c /4.5 Hours	
		43:68 mg/l, 6 Hours	
	Mouse	> 60000 ppm	
	**	79.43 mg/l, 134 Minutes	
	Rat	> 115.9 mg/l _i 4 Hours	
		51.3 mg/l, 6 Hours	
Oral			
LD50	Monkey	6000 mg/kg	
	Mouse	10500 ml/kg	
	Rat	1187 - 2769 mg/kg	
		.7800 ml/kg	
		~	

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation

Not expected to be hazardous by OSHA criteria.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization

Not available.

Skin sensitization

This product is not expected to cause skin sensitization.

Germ cell mutagenicity

Not expected to be hazardous by OSHA criteria.

Carcinogenicity

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified

Aspiration hazard

Not likely, due to the form of the product.

Product name: MULTI-PURPOSE ANTI-STATIC SPRAY

Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity

LC50: 16191 mg/L, Fish, 96.00 Hours EC50: 14503 mg/L, Daphnia, 48.00 Hours

Test Results Species Product MULTI-PURPOSE ANTI-STATIC SPRAY (CAS Mixture)

Aquatic

Algae IC50 Algae

Crustacea EC50 Daphnia 14503 mg/L, 48 Hours Fish LC50 Fish 16191 mg/L, 96 Hours

Components Species **Test Results**

Ethyl Alcohol (CAS 64-17-5)

Aquatic

Crustacea EC50

Water flea (Daphnia magna)

7700 - 11200 mg/l, 48 hours

SDS US

72 Hours

Fish

LC50

Fathead minnow (Pimephales promelas) > 100.1 mg/l, 96 hours

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

No data available.

Partition coefficient n-octanol / water (log Kow)

1,1-Difluoroethane

0.75

Ethyl Alcohol

-0.31

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers,

14. Transport information

DOT

UN1950 **UN number** UN proper shipping name

Transport hazard class(es)

Aerosols

Class

2.1

Subsidiary risk Label(s)

None:

Packing group

Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions

153, N82 LTD QTY

Packaging exceptions Packaging non bulk

None

Packaging bulk None

Product name: MULTI-PURPOSE ANTI-STATIC SPRAY

^{*} Estimates for product may be based on additional component data not shown.

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number

UN proper shipping name

Aerosols, flammable

Transport hazard class(es)

Class Subsidiary risk 2.1

Label(s)

2.1

Packing group

Not applicable.

Environmental hazards

Yes

ERG Code

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed.

aircraft

Cargo aircraft only

Allowed.

Packaging Exceptions

LTD QTY

IMDG

UN number

UN1950 **AEROSOLS**

UN proper shipping name Transport hazard class(es)

Class

2.1

Subsidiary risk

Label(s)

None

Packing group

Not applicable.

Environmental hazards

Marine pollutant

Yes

EmS

Not available.

Not applicable.

Packaging Exceptions

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

LTD QTY

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT







Product name: MULTI-PURPOSE ANTI-STATIC SPRAY

Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No.

chemical

SARA 313 (TRI reporting)

Chemical name

CAS number

% by wt.

t-Butyl Alcohol

75-65-0

0.1 - 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

1,1-Difluoroethane (CAS 75-37-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

1,1-Difluoroethane (CAS 75-37-6)

Ethyl Alcohol (CAS 64-17-5)

US. New Jersey Worker and Community Right-to-Know Act

1,1-Difluoroethane (CAS 75-37-6)

Ethyl Alcohol (CAS 64-17-5)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethyl Alcohol (CAS 64-17-5)

US. Rhode Island RTK

1,1-Difluoroethane (CAS 75-37-6)

Product name: MULTI-PURPOSE ANTI-STATIC SPRAY

SDS US

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive fram.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 05-29-2015

Version #

Disclaimer

Sprayway cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume flability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.