MATERIAL SAFETY DATA SHEET
This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFACTURER'S INFORMATION						
NFPA Rating: Health-2; Flammability-0; Reactivity-0; Special HMIS Rating: Health-2; Flammability-0; Reactivity-0; Personal Protection-B						
Manufactured For: Hillyard Industries, Inc.	DOT Hazard Classification: ORM-D					
	Identity (trade name as used on label):					
Address: St. Joseph, MO 64501	I-Force Safety Solvent					
·	(# HIL0110854)					
Phone: (816)-233-1321 ext. 8285 or http://www.hillyard.com	: (816)-233-1321 ext. 8285 or http://www.hillyard.com MSDS Number: A00365 Revision- 15					
EMERGENCY RESPONSE NUMBER: Chemtrec 1-800-424-9300	pared: 07/1/05 Prepared By: LF/DL/IB					
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA Information Calls: (770)422-2071						
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES		CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)			III LIST	(ppm)	TLV (ppm)	Ref. Source **
PERCHLOROETHYLENE		127-18-4	Yes	25	25	a,b
ACETONE		67-64-1	No	1000	750	d
CARBON DIOXIDE		124-38-9	No	5000	5000	d
WARNING: This product contains a chemical or chemicals known to the State of California to cause cancer.						
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS						
Boiling Point: N/A Specific Gravity (H2O=1): Concentrate Only = 1.60 Vapor Pressure: PSIG @ 70°F (Aerosols): 85-100 Vapor Pressure (Non-Aerosols) (mm Hg and Temperature): N/A						
Vapor Pressure: PSIG @ 70 P (Aerosols). 05-100						
Solubility in Water: Insoluble Water Reactive: No						
Appearance and Odor: Clear, colorless spray with chlorinated solvent odor.						
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA						
LAMMABILITY as per USA FLAME PROJECTION TEST Auto Ignition Temperature Flammability Limits in Air by % in Volume:						
aerosols) NON-FLAMMABLE N/E % LEL: N/E % UEL						
FLASH POINT AND METHOD USED (non-aerosols): N/A	EYI					
FLASH POINT AND METHOD USED (non-aerosols): N/A SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus. EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide.						
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.						
SECTION 4 - REACTIVITY HAZARD DATA						
STABILITY [X] STABLE [] UNSTABLE HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR						
Incompatibility (Mat. to avoid): Reactive metals, aluminum, magnesium, strong oxidizing agents. Conditions to Avoid: Open flame, welding arcs, heat.						
Hazardous Decomposition Products: CO2, CO, HCl, small amounts of phosgene and chlorine.						
SECTION 5 - HEALTH HAZARD DATA						
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION [X]SKIN ABSORPTION []EYE []NOT HAZARDOUS ACUTE EFFECTS:						
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.						
Eye Contact: Irritation due to defatting of skin.						
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.						
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause liver abnormalities, kidney, spleen, lung or brain						
damage, cardiac abnormalities. Perchloroethylene has been shown to increase the rate of spontaneously occurring malignant tumors in certain laboratory rats and mice.						
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions. EMERGENCY FIRST AID PROCEDURES						
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.						
Skin Contact: Wash with soap and water. If irritated, seek medical attention.						
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.						
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.						
SECTION 6 - CONTROL AND PROTECTIVE MEASURES						
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor.						
Protective Gloves: Neoprene gloves recommended. Eye Protection: Safety glasses recommended.						
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.						
Other Protective Clothing & Equipment: None						
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.						
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE						
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or Federal regulations. Allow to evaporate if small spill. DO NOT FLUSH TO SEWER.						
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.						
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.						
Other Precautions & or Special Hazards: KEEP OUT OF REACH OF CHILDREN, Avoid food contamination, Avoid inhalation of vapors						

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only