

# Safety Data Sheet

Issue date 05-Jun-2018

Revision date 07-Nov-2022

Revision Number 2

## 1. IDENTIFICATION

### Product identification

Product identifier Lawson Ford Tractor Blue Industrial Paint  
 Other means of identification 1509212  
 Recommended use Paint  
 Restrictions on use Not applicable

### Supplier

Corporate Headquarters:  
 Lawson Products, Inc.  
 8770 W. Bryn Mawr Ave., Suite 900  
 Chicago, IL 60631  
 (866) 837-9908

Canadian Distribution Center:  
 Lawson Canada  
 7315 Rapistan Court  
 Mississauga, ON L5N 5Z4  
 (800) 323-5922

**24 Hour Emergency Phone Number** (888) 426-4851 (Prosar)

**Website** [www.lawsonproducts.com](http://www.lawsonproducts.com)

## 2. HAZARD(S) IDENTIFICATION

### Hazard Classification

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), WHMIS 2015 and GHS Regulations.

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable aerosols	Category 1
Gases under pressure	Compressed gas

### Symbol



### Signal word

DANGER

### Hazard statements

H222 - Extremely flammable aerosol  
 H280 - Contains gas under pressure; may explode if heated

H319 - Causes serious eye irritation  
 H336 - May cause drowsiness or dizziness  
 H373 - May cause damage to organs through prolonged or repeated exposure  
 H315 - Causes skin irritation  
 H361 - Suspected of damaging fertility or the unborn child

**Precautionary statements**

**General**

P101 - If medical advice is needed, have product container or label at hand  
 P103 - Read label before use.  
 P102 - Keep out of reach of children

**Prevention**

P201 - Obtain special instructions before use  
 P202 - Do not handle until all safety precautions have been read and understood  
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 - Do not spray on an open flame or other ignition source  
 P251 - Pressurized container: Do not pierce or burn, even after use  
 P264 - Wash hands thoroughly after handling  
 P271 - Use only outdoors or in a well-ventilated area  
 P280 - Wear protective gloves/protective clothing and eye/face protection  
 P260 - Do not breathe dust/fume/gas/mist/vapors/spray

**Response**

**General**

P312 - Call a POISON CENTER or doctor if you feel unwell

**Eyes**

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 P337 + P313 - If eye irritation persists: Get medical advice/attention

**Skin**

P332 + P313 - If skin irritation occurs: Get medical advice/attention  
 P302 + P352 - IF ON SKIN: Wash with plenty of soap and water  
 P362 - Take off contaminated clothing and wash before reuse

**Inhalation**

P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

**Storage**

P405 - Store locked up  
 P412 - Do not expose to temperatures exceeding 50 °C/122 °F  
 P410 - Protect from sunlight  
 P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

**Disposal**

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

**Hazard(s) Not Otherwise Classified (HNOC)**

None known.

**Physical Hazards Not Otherwise Classified (PHNOC)**

None known.

**Unknown acute toxicity**

None known.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Composition**

This product is a mixture of the substances listed below with nonhazardous additions.

Chemical name	CAS-No	Weight %
---------------	--------	----------

Acetone	67-64-1	39.62
Propane	74-98-6	15.75
Toluene	108-88-3	12.44
N-Butane	106-97-8	9.25
Methylisobutyl ketone	108-10-1	2.19
Methyl Propyl Ketone	107-87-9	1.93
Ethylene glycol monopropyl ether	2807-30-9	1.62
Titanium Dioxide	13463-67-7	1.03
Ethyl benzene	100-41-4	<1
Carbon Black	1333-86-4	<1

#### 4. FIRST-AID MEASURES

##### Necessary first-aid measures

<b>Inhalation</b>	Supply fresh air. Consult doctor in case of complaint.
<b>Ingestion</b>	Rinse mouth with water. Do NOT induce vomiting.
<b>Skin contact</b>	Remove contaminated clothing. Wash exposed area with soap and water.
<b>Eye contact</b>	Rinse opened eye for several minutes under running water. If symptoms persist, call a physician.

**Most important symptoms (acute)** Dizziness.

**Most important symptoms (over-exposure)** No further relevant information available.

**Indication of any immediate medical attention and special treatment needed** No further relevant information available.

#### 5. FIRE-FIGHTING MEASURES

<b>Suitable extinguishing media</b>	Carbon dioxide (CO <sub>2</sub> ). Extinguishing powder. Water spray. Fight larger fires with water spray.
<b>Unsuitable extinguishing media</b>	Not available.
<b>Specific hazards</b>	Can form explosive gas-air mixtures.
<b>Special protective equipment for fire-fighters</b>	A respiratory protective device may be necessary.

#### 6. ACCIDENTAL RELEASE MEASURES

<b>Personal precautions, protective equipment and emergency procedures</b>	Use respiratory protective device against the effects of fumes/dust/aerosol.
<b>Methods and materials for containment and cleaning up</b>	Dispose contaminated material as waste according to section 13.

#### 7. HANDLING AND STORAGE

**Precautions for safe handling** Use only in a well ventilated area.

**Conditions for safe storage, including any incompatibilities** Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

Chemical name	OSHA PEL (TWA)	California - PELs	ACGIH OEL (TWA)	NIOSH - TWA
Acetone	1000 ppm TWA 2400 mg/m <sup>3</sup> TWA	500 ppm PEL; 1200 mg/m <sup>3</sup> PEL	250 ppm TWA	250 ppm TWA 590 mg/m <sup>3</sup> TWA
Propane	1000 ppm TWA 1800 mg/m <sup>3</sup> TWA	1000 ppm PEL; 1800 mg/m <sup>3</sup> PEL		1000 ppm TWA 1800 mg/m <sup>3</sup> TWA 1000 ppm TWA 1800 mg/m <sup>3</sup> TWA
Toluene	200 ppm TWA	10 ppm PEL; 37 mg/m <sup>3</sup> PEL	20 ppm TWA	100 ppm TWA 375 mg/m <sup>3</sup> TWA
N-Butane	-	800 ppm PEL; 1900 mg/m <sup>3</sup> PEL		800 ppm TWA 1900 mg/m <sup>3</sup> TWA 1000 ppm TWA 1800 mg/m <sup>3</sup> TWA
Methylisobutyl ketone	100 ppm TWA 410 mg/m <sup>3</sup> TWA	50 ppm PEL; 205 mg/m <sup>3</sup> PEL	20 ppm TWA	50 ppm TWA 205 mg/m <sup>3</sup> TWA
Methyl Propyl Ketone	200 ppm TWA 700 mg/m <sup>3</sup> TWA	200 ppm PEL; 700 mg/m <sup>3</sup> PEL		150 ppm TWA 530 mg/m <sup>3</sup> TWA
Ethylene glycol monopropyl ether	-			
Titanium Dioxide	15 mg/m <sup>3</sup> TWA	5 mg/m <sup>3</sup> PEL (respirable fraction, listed under Particulates not otherwise regulated); 10 mg/m <sup>3</sup> PEL (total dust, listed under Particulates not otherwise regulated)	0.2 mg/m <sup>3</sup> TWA 2.5 mg/m <sup>3</sup> TWA	2.4 mg/m <sup>3</sup> TWA 0.3 mg/m <sup>3</sup> TWA
Ethyl benzene	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	5 ppm PEL; 22 mg/m <sup>3</sup> PEL	20 ppm TWA	100 ppm TWA 435 mg/m <sup>3</sup> TWA
Carbon Black	3.5 mg/m <sup>3</sup> TWA	3.5 mg/m <sup>3</sup> PEL	3 mg/m <sup>3</sup> TWA	3.5 mg/m <sup>3</sup> TWA 0.1 mg/m <sup>3</sup> TWA

**Appropriate engineering controls** Not available.

**Individual protection measures, such as personal protective equipment**

**Eye protection** Tightly fitting safety goggles.

**Skin and body protection** Nitrile gloves. Protective gloves. The glove material must be impermeable and resistant to the substance.

**Respiratory protection** A respirator is generally not necessary when using this product outdoors or in a large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hygiene measures** Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with skin and eyes. Do not eat or drink while working.

**Canadian Province Occupational Exposure Limits**

Chemical name	AB	BC	MB	NB	NL	NS	ON	PE	QC	SK
Acetone	500 ppm TWA 1200 mg/m <sup>3</sup> TWA	250 ppm TWA	250 ppm TWA	500 ppm TWA 1188 mg/m <sup>3</sup> TWA	250 ppm TWA	250 ppm TWA	250 ppm TWA	250 ppm TWA	500 ppm TWAEV 1190 mg/m <sup>3</sup> TWAEV	500 ppm TWA
Propane	1000 ppm TWA 1640 mg/m <sup>3</sup> TWA	1000 ppm TWA	-	1000 ppm TWA 1640 mg/m <sup>3</sup> TWA	-	-	-	-	1000 ppm TWAEV 1800 mg/m <sup>3</sup> TWAEV 1000 ppm TWAEV 1640 mg/m <sup>3</sup> TWAEV	1000 ppm TWA 1000 ppm TWA 1000 ppm TWA
Toluene	50 ppm TWA 188 mg/m <sup>3</sup> TWA	20 ppm TWA	20 ppm TWA	50 ppm TWA 188 mg/m <sup>3</sup> TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	50 ppm TWAEV 188 mg/m <sup>3</sup> TWAEV	50 ppm TWA
N-Butane	1000 ppm TWA 1640 mg/m <sup>3</sup> TWA	1000 ppm TWA	-	800 ppm TWA 1900 mg/m <sup>3</sup> TWA 1000 ppm TWA 1640 mg/m <sup>3</sup> TWA	-	-	-	-	800 ppm TWAEV 1900 mg/m <sup>3</sup> TWAEV 1000 ppm TWAEV 1640 mg/m <sup>3</sup> TWAEV	1000 ppm TWA 1000 ppm TWA 1000 ppm TWA 1000 ppm TWA
Methylisobutyl ketone	50 ppm TWA 205 mg/m <sup>3</sup> TWA	20 ppm TWA	20 ppm TWA	50 ppm TWA 205 mg/m <sup>3</sup> TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	20 ppm TWAEV	50 ppm TWA
Methyl Propyl Ketone	200 ppm TWA 705 mg/m <sup>3</sup> TWA	150 ppm TWA	-	200 ppm TWA 705 mg/m <sup>3</sup> TWA	-	-	-	-	150 ppm TWAEV 530 mg/m <sup>3</sup> TWAEV	200 ppm TWA
Ethylene glycol monopropyl ether	-	-	-	-	-	-	25 ppm TWA 110 mg/m <sup>3</sup> TWA	-	-	-
Titanium Dioxide	10 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> TWA 3 mg/m <sup>3</sup> TWA	0.2 mg/m <sup>3</sup> TWA 2.5 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> TWA	0.2 mg/m <sup>3</sup> TWA 2.5 mg/m <sup>3</sup> TWA	0.2 mg/m <sup>3</sup> TWA 2.5 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> TWA	0.2 mg/m <sup>3</sup> TWA 2.5 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> TWAEV	10 mg/m <sup>3</sup> TWA
Ethyl benzene	100 ppm TWA 434 mg/m <sup>3</sup> TWA	20 ppm TWA	20 ppm TWA	100 ppm TWA 434 mg/m <sup>3</sup> TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	20 ppm TWAEV	100 ppm TWA
Carbon Black	3.5 mg/m <sup>3</sup> TWA	3 mg/m <sup>3</sup> TWA	3 mg/m <sup>3</sup> TWA	3.5 mg/m <sup>3</sup> TWA	3 mg/m <sup>3</sup> TWA	3 mg/m <sup>3</sup> TWA	3 mg/m <sup>3</sup> TWA	3 mg/m <sup>3</sup> TWA	3 mg/m <sup>3</sup> TWAEV	3.5 mg/m <sup>3</sup> TWA

### 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state</b>	Aerosol
<b>Color</b>	Blue
<b>Odor</b>	Aromatic
<b>Odor threshold</b>	Not available
<b>pH</b>	Not available
<b>Melting point/range °C</b>	Not available
<b>Melting point/range °F</b>	Not available
<b>Boiling point/range °C</b>	-44 °C

<b>Boiling point/range °F</b>	-47 °F
<b>Flash point °C</b>	-19
<b>Flash point °F</b>	-2
<b>Flash point method used</b>	Not available
<b>Evaporation rate</b>	Not available
<b>Flammability (Solid, Gas)</b>	Extremely flammable
<b>Lower explosion limit</b>	1.7 %
<b>Upper explosion limit</b>	10.9 %
<b>Vapor pressure</b>	Not available
<b>Vapor density</b>	Not available
<b>Relative density</b>	0.77-0.85
<b>Solubility</b>	Not available
<b>Partition coefficient (n-octanol/water)</b>	Not available
<b>Autoignition temperature °C</b>	Product is not self-igniting
<b>Autoignition temperature °F</b>	Product is not self-igniting
<b>Decomposition temperature °C</b>	Not available
<b>Decomposition temperature °F</b>	Not available
<b>Viscosity</b>	Not available

## 10. STABILITY AND REACTIVITY

<b>Reactivity</b>	Stable at normal temperatures.
<b>Chemical stability</b>	Not fully evaluated. In use, may form flammable/explosive vapour-air mixture.
<b>Possibility of hazardous reactions</b>	None known.
<b>Conditions to avoid</b>	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing conditions.
<b>Incompatible materials</b>	No further relevant information available.
<b>Hazardous decomposition products</b>	None known.

## 11. TOXICOLOGICAL INFORMATION

<b>Information on likely routes of exposure</b>	Eyes.
<b>Symptoms</b>	Eye irritation.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure** No sensitizing effects known. No skin irritant effect. Causes eye irritation.

#### Numerical measures of toxicity

Chemical name	Inhalation LC50:	Dermal LD50:	Oral LD50:
Acetone	50100 mg/m <sup>3</sup> Rat	= 5800 mg/kg Rat >15700 mg/kg Rabbit	5800 mg/kg ( Rat )
Propane	658 mg/L (Rat) 4h	-	-
Toluene	12.5 mg/L/4h (Rat)	8390 mg/kg (Rabbit)	636 mg/kg (Rat)
N-Butane	658 g/m <sup>3</sup> Rat	-	-
Methylisobutyl ketone	2000 - 4000 ppm Rat	= 2080 mg/kg Rat 3000 mg/kg Rabbit	2080 mg/kg Rat = 3000 mg/kg Rabbit
Methyl Propyl Ketone	2000 - 4000 ppm Rat	= 1600 mg/kg Rat 6480 mg/kg Rat	1600 mg/kg Rat = 6480 mg/kg Rat = 6500 mg/kg Rabbit
Ethylene glycol monopropyl ether	1530 ppm Rat	= 3089 mg/kg Rat 870 mg/kg Rabbit	3089 mg/kg Rat = 870 mg/kg Rabbit = 960 µL/kg Rabbit
Titanium Dioxide	5.09 mg/L Rat	> 10000 mg/kg Rat	>10000 mg/kg Rat
Ethyl benzene	= 17.2 mg/L ( Rat ) 4 h	15354 mg/kg ( Rabbit )	= 3500 mg/kg ( Rat )
Carbon Black	>4.6 mg/m <sup>3</sup> Rat	> 15400 mg/kg Rat	>15400 mg/kg Rat

**ATEmix (dermal)** Not available

**ATEmix (oral)** Not available

**ATEmix (inhalation-gas)** Not available

**ATEmix (inhalation-vapor)** Not available

**ATEmix (inhalation-dust/mist)** Not available

#### Carcinogenicity

Chemical name	ACGIH OEL - Carcinogens	IARC	OSHA Carcinogens	NTP
Acetone	A4	-	-	-
Propane	-	-	-	-
Toluene	A4	Group 3	-	-
N-Butane	-	-	-	-
Methylisobutyl ketone	A3	Group 2B	Present	-
Methyl Propyl Ketone	-	-	-	-
Ethylene glycol monopropyl ether	-	-	-	-
Titanium Dioxide	A3	Group 2B	Present	-
Ethyl benzene	A3	Group 2B	X	-
Carbon Black	A3	Group 2B	Present	-

#### Canadian Province carcinogenicity limits

Chemical name	Alberta - Carcinogen	British Columbia - Carcinogen	Manitoba - Carcinogen	New Brunswick - Carcinogen	Nova Scotia - Carcinogen	Quebec - Carcinogen

Chemical name	Alberta - Carcinogen	British Columbia - Carcinogen	Manitoba - Carcinogen	New Brunswick - Carcinogen	Nova Scotia - Carcinogen	Quebec - Carcinogen
Acetone	-	-	ACGIH A4	ACGIH A4	ACGIH A4	-
Propane	-	-	-	-	-	-
Toluene	-	-	ACGIH A4	ACGIH A4	ACGIH A4	-
N-Butane	-	-	-	-	-	-
Methylisobutyl ketone	-	IARC 2B	ACGIH A3	-	ACGIH A3	C3 Carcinogen
Methyl Propyl Ketone	-	-	-	-	-	-
Ethylene glycol monopropyl ether	-	-	-	-	-	-
Titanium Dioxide	-	IARC 2B	ACGIH A3	ACGIH A4	ACGIH A3	-
Ethyl benzene	-	IARC 2B	ACGIH A3	-	ACGIH A3	C3 Carcinogen
Carbon Black	-	IARC 2B	ACGIH A3	ACGIH A4	ACGIH A3	C3 Carcinogen

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Hazardous for water, do not empty into drains.

Chemical name	Algae/aquatic plants	Fish LC50
Acetone	-	4.74 - 6.33mL/L Oncorhynchus mykiss 96h 6210 - 8120mg/L Pimephales promelas 96h = 8300mg/L Lepomis macrochirus 96h
Propane	-	-
Toluene	=12.5mg/L Pseudokirchneriella subcapitata 72h >433mg/L Pseudokirchneriella subcapitata 96h	11.0 - 15.0mg/L Lepomis macrochirus 96h 14.1 - 17.16mg/L Oncorhynchus mykiss 96h 15.22 - 19.05mg/L Pimephales promelas 96h 5.89 - 7.81mg/L Oncorhynchus mykiss 96h 50.87 - 70.34mg/L Poecilia reticulata 96h = 12.6mg/L Pimephales promelas 96h = 28.2mg/L Poecilia reticulata 96h = 5.8mg/L Oncorhynchus mykiss 96h = 54mg/L Oryzias latipes 96h
N-Butane	-	-
Methylisobutyl ketone	=400mg/L Pseudokirchneriella subcapitata 96h	496 - 514mg/L Pimephales promelas 96h
Methyl Propyl Ketone	-	1190 - 1290mg/L Pimephales promelas 96h
Ethylene glycol monopropyl ether	-	> 5000mg/L Pimephales promelas 96h
Titanium Dioxide	-	-
Ethyl benzene	=4.6mg/L Pseudokirchneriella subcapitata 72h >438mg/L Pseudokirchneriella subcapitata 96h 2.6 - 11.3mg/L Pseudokirchneriella subcapitata 72h 1.7 - 7.6mg/L Pseudokirchneriella subcapitata 96h =11mg/L Pseudokirchneriella subcapitata 72h	11.0 - 18.0mg/L Oncorhynchus mykiss 96h 7.55 - 11mg/L Pimephales promelas 96h 9.1 - 15.6mg/L Pimephales promelas 96h = 32mg/L Lepomis macrochirus 96h = 4.2mg/L Oncorhynchus mykiss 96h = 9.6mg/L Poecilia reticulata 96h
Carbon Black	-	-

**Persistence and degradability** The product is degradable after prolonged exposure to natural weathering processes.

### Bioaccumulation

Chemical name	CAS-No	Partition coefficient (log Kow)	Bioconcentration factor (BCF)
Acetone 67-64-1	67-64-1	-0.24	0.69 dimensionless species: fish
Propane 74-98-6	74-98-6	2.3 <=2.8	-
Toluene	108-88-3	2.73 at 20 °C (at pH 7,	-

Chemical name	CAS-No	Partition coefficient (log Kow)	Bioconcentration factor (BCF)
108-88-3		ECHA_API 3.44 at 25 °C (at pH 7, ECHA_API); 3.93 at 20 °C (at pH 7, ECHA_API)	
N-Butane 106-97-8	106-97-8	2.31 at 20 °C (at pH 7, ECHA_API) ≤2.8	-
Methylisobutyl ketone 108-10-1	108-10-1	1.9 [OECD Guideline 117] (at pH 6.7, ECHA_API)	-
Methyl Propyl Ketone 107-87-9	107-87-9	0.857 at 20 °C [OECD Guideline 107] (at pH 7, ECHA_API)	-
Ethylene glycol monopropyl ether 2807-30-9	2807-30-9	0.673 at 40 °C [Directive 84/449/EEC, A.8] (at pH 7, ECHA_API)	-
Titanium Dioxide 13463-67-7	13463-67-7	-	-
Ethyl benzene 100-41-4	100-41-4	3.6 at 20 °C [Directive 84/449/EEC, A.8] (at pH 7.84, ECHA_API)	15 dimensionless species: fish
Carbon Black 1333-86-4	1333-86-4	-	-

**Mobility in soil** Not available.

**Other adverse effects** Not available

**13. DISPOSAL CONSIDERATIONS**

**Disposal information** Dispose of in accordance with federal, state and local regulations. Do not puncture, incinerate, or crush. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

**Contaminated packaging** Completely empty cans should be recycled.

**14. TRANSPORTATION INFORMATION**

**Shipping Descriptions**

**DOT**

ID-No UN1950  
 Proper shipping name Aerosols, flammable  
 Hazard Class(es) 2.1  
 Special Provisions LTD QTY

**TDG**

ID-No UN1950  
 Proper shipping name Aerosols, flammable  
 Hazard Class(es) 2.1  
 Special Provisions LTD QTY

**IATA**

ID-No UN1950  
 Proper shipping name Aerosols, flammable  
 Hazard Class(es) 2.1  
 Special Provisions LTD QTY

**IMDG/IMO**

ID-No UN1950  
 Proper shipping name Aerosols

Hazard Class(es)  
Special Provisions

2.1  
LTD QTY

### Marine Pollutants

Chemical name	CAS-No	USDOT Marine Pollutant	Canada TDG Marine Pollutant	IMDG Marine Pollutant
Acetone	67-64-1	-	-	-
Propane	74-98-6	-	-	-
Toluene	108-88-3	-	-	-
N-Butane	106-97-8	-	-	-
Methylisobutyl ketone	108-10-1	-	-	-
Methyl Propyl Ketone	107-87-9	-	-	-
Ethylene glycol monopropyl ether	2807-30-9	-	-	-
Titanium Dioxide	13463-67-7	-	-	-
Ethyl benzene	100-41-4	-	-	-
Carbon Black	1333-86-4	-	-	-

### Special Precautions

Multi-modal shipping descriptions are provided for informational purposes and do not consider container size. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

## 15. REGULATORY INFORMATION

### State regulations

#### U.S. state Right-to-Know regulations

Chemical name	CAS-No	Massachusetts - RTK	New Jersey - RTK	Pennsylvania - RTK
Acetone	67-64-1	X	X	X
Propane	74-98-6	X	X	X
Toluene	108-88-3	X	X	X
N-Butane	106-97-8	X	X	X
Methylisobutyl ketone	108-10-1	X	X	X
Methyl Propyl Ketone	107-87-9	X	X	X
Ethylene glycol monopropyl ether	2807-30-9	-	X	X
Titanium Dioxide	13463-67-7	X	X	X
Ethyl benzene	100-41-4	X	X	X
Carbon Black	1333-86-4	X	X	X

#### California Prop. 65

Chemical name	CAS-No	California Prop. 65
Acetone	67-64-1	-
Propane	74-98-6	-
Toluene	108-88-3	Developmental
N-Butane	106-97-8	-
Methylisobutyl ketone	108-10-1	Carcinogen Developmental
Methyl Propyl Ketone	107-87-9	-
Ethylene glycol monopropyl ether	2807-30-9	-

Chemical name	CAS-No	California Prop. 65
Titanium Dioxide	13463-67-7	Carcinogen
Ethyl benzene	100-41-4	Carcinogen
Carbon Black	1333-86-4	Carcinogen

## U.S. Federal Regulations

Consumer Product Safety  
Commission

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

## US EPA SARA 313

Chemical name	CAS-No	CERCLA/SARA Hazardous Substances RQ	SARA 313 - Threshold Values
Acetone	67-64-1	5000 lb 2270 kg	-
Propane	74-98-6	-	-
Toluene	108-88-3	1000 lb 454 kg 1 lb 0,454 kg	1.0 %
N-Butane	106-97-8	-	-
Methylisobutyl ketone	108-10-1	5000 lb 2270 kg	0.1 %
Methyl Propyl Ketone	107-87-9	-	-
Ethylene glycol monopropyl ether	2807-30-9	-	1.0 %
Titanium Dioxide	13463-67-7	-	-
Ethyl benzene	100-41-4	1000 lb 454 kg	0.1 %
Carbon Black	1333-86-4	-	-

US EPA SARA 311/312  
hazardous categorization

Not available

## TSCA and Canadian Inventories

Chemical name	Inventory - United States - Section 8(b) Inventory (TSCA)	U.S. - TSCA (Toxic Substances Control Act) - Section 12(b) - Export Notification	DSL	NDSL
Acetone	X	-	X	-
Propane	X	-	X	-
Toluene	X	-	X	-
N-Butane	X	-	X	X
Methylisobutyl ketone	X	-	X	-
Methyl Propyl Ketone	X	-	X	-
Ethylene glycol monopropyl ether	X	-	X	-
Titanium Dioxide	X	-	X	-
Ethyl benzene	X	-	X	-
Carbon Black	X	-	X	-

Legend X - Listed

## 16. OTHER INFORMATION

**NFPA**

<b>Health</b>	Not available
<b>Flammability</b>	Not available
<b>Instability</b>	Not available

**HMIS**

<b>Health</b>	Not available
<b>Flammability</b>	Not available
<b>Physical hazards</b>	Not available

Notice: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA).

**Prepared by** Regulatory Affairs

**Issue date** 05-Jun-2018

**Revision date** 07-Nov-2022

**Revision note****Key to abbreviations**

ACGIH (American Conference of Governmental Industrial Hygienists)  
 ATE (Average Toxicity Estimate)  
 DSL/NDSL (Domestic Substance List/Non-Domestic Substance List)  
 HMIS (Hazardous Materials Identification System)  
 IARC (International Agency for Research on Cancer)  
 IATA (International Air Transport Association)  
 IMDG/IMO (International Maritime Dangerous Goods/International Maritime Organization)  
 NFPA (National Fire Protection Association)  
 NTP (National Toxicology Program)  
 OEL (Occupational Exposure Level)  
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)  
 PEL (Permissible Exposure Limit)  
 TSCA (Toxic Substance Control Act)  
 USEPA (United States Environmental Protection Agency)

**Disclaimer**

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

End of Safety Data Sheet