## **Material Safety Data Sheet**

00116CA Construction Adhesive – Solvent Free – 28 oz cartridge

MSDS No. 0076	-00116CA					gency Pho 5-5053 - INI	
	SECTION 1 – I	PRODUCT NAME & I	MANUFACTURER	INFORM	ATION		
PRODUCT NAME		esive – Solvent Free – VOC Complia					
MANUFACTURER'S N TELEPHONE NUMBEI		918-825-5744					
STREET ADDRESS	4175 Webb Street						
CITY / STATE / ZIP	Pryor, Oklahoma	74361					
SECTIO	ON 2 – COMPOSIT	ION/HAZARDOUS	NGREDIENTS	%	TLV	PEL	UNITS
PRODUCT CONSISTS	OF:						
Calcium Carb	onate ** (1317-65-3)			< 50	10	15	mg/m3
Acrylic Emulsion (mixture)				< 35	NE	NE	
Benzoate Este				<5	NE	NE	
	Hydroxide (7664-41-7)			< 0.25	25	50	ppm
Ammonium 1	Tythoxide (7004-41-7)						
1910.1200). *	**Inhalation not likely due to pr	rclous under the OSHA Hazard Con oducts physical state. 3 Compliance: Yes. Prop 65 Ingredi					
		SECTION 3 – HAZAR	DS IDENTIFICATI	ON			
PRIMARY ROUTE(S) OF ENTRY	Skin Contact	Skin Absorption	Eye Contact	⊠ Inhala	ition	⊠ Ing	gestion
EMERGENCY							
OVERVIEW	Off-white colored paste pro	duct. Harmful if swallowed.			,		
EFFECTS OF OVEREXPOSURE		duct. Harmful if swallowed.  hroat & respiratory tract irritation.			3		
EFFECTS OF					•		
EFFECTS OF OVEREXPOSURE MEDICAL CONDITIONS AGGRAVATED BY	May cause eye, skin, nose,	hroat & respiratory tract irritation.	ST AID MEASURES				
EFFECTS OF OVEREXPOSURE MEDICAL CONDITIONS AGGRAVATED BY	May cause eye, skin, nose, l	hroat & respiratory tract irritation.			v wash contain	minated clot	hing.
EFFECTS OF OVEREXPOSURE MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE	May cause eye, skin, nose, s  None known.  Wash w/ soap	hroat & respiratory tract irritation.  SECTION 4 – FIRS	medical attention if symptoms [	persist. Remove &	SANSAL SANSA		hing.
EFFECTS OF OVEREXPOSURE MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE	May cause eye, skin, nose, when the second s	section 4 – FIRS  & water for @ least 15 minutes. Get	medical attention if symptoms p	persist. Remove &	edical attenti	on.	hing.

	SECTION 5 – FII	RE FIGHTING M	IEASURES
FLAMMABLE Yes	⊠ No		
EXTINGUISHING	rbon Dioxide, Dry Chemical, Foam, Water Fog		
MEDIA  FLASHPOINT (°F) &	>200F (Closed Cup)	UPPER EXPLOSIV	E LIMIT NE
METHOD  LOWER EXPLOSIVE LIMIT	NE	(% BY VOLUME) AUTOIGNITION	NE
(% BY VOLUME) UNUSUAL FIRE & EXPLOSION	None known.	TEMPERTURE (°F	
HAZARDS  SPECIAL We FIREFIGHTING PROCEDURES	ear self-contained breathing apparatus pressure de cool exposed surfaces.	mand (NIOSH approved or	equivalent) & full protective gear. Use water spray to
- Koedine Has	SECTION 6 - ACCID	ENTAL RELEAS	SE MEASURES
PROCEDURES We	ear proper protective equipment (Section 8). Use a	absorbent material or scrape	up dried material & place in approved container.
		HANDLING & ST	
HANDLING PROCEDURES & EQUIPMENT	Keep out of reach of children & pets. Do not tak thoroughly after handling. Avoid con fresh air during application & curing	ntact w/ eyes, skin & clothin	vapors. Use only w/ adequate ventilation. Wash g. Open windows & doors to ensure cross-ventilation &
STORAGE REQUIREMENTS	Close container after each use. Store containers away from caustics & oxidizers.	away from excessive heat &	freezing. Do not store @ temperatures above 120F. Store
	SECTION 8 – EXPOSURE C	ONTROL/PERS	SONAL PROTECTION
	insufficient ventilation, wear suitable respiratory under circumstances where concentrations are ex		ved air purifying respirator w/ organic vapor cartridge may be mits.
EYEWEAR Goggles of	r safety glasses w/ side shields.		
CLOTHING / Rubber gloves	oves. Other protective equipment not required une	der normal use.	
HYGENIC Remove &	wash contaminated clothing before re-use. Wash	n hands before breaks & @ e	end of workday.
	SECTION 9 – PHYSICA	L AND CHEMIC	CAL PROPERTIES
PHYSICAL STATE	Viscous paste	ODOR & APPEARANCE	Mild acrylic/ammonia. Smooth paste.
SPECIFIC GRAVITY	Approximately 1.0 to 1.50	VAPOR DENSITY (AIR=1)	Heavier than air
EVAPORATION RATE	Slower than n-Butyl Acetate	BOILING RANGE (°F)	210 to 220F
рН	Approximately 7 to 10	SOLUBILITY IN WATER	Slight, before cure.
VAPOR PRESSURE (MM Hg)	NE	· %/WT VOLATILE (TNV)	Approximately 25 to 30%
	SECTION 10 – ST	ABILITY AND R	EACTIVITY .
STABILITY Yes	No Stable under normal conditions.		
INCOMPATABILITY	Yes No Incompatible w/ st	trong bases & oxidizing ager	nts.
CONDITIONS Excessive h	eat & freezing.		
HAZARDOUS POLYMERIZATION/HAZARDOU DEGOMPOSITION PRODUCTS	Hazardous polymerization will not occur u	under normal conditions. No	ormal decomposition products, ie: COx, NOx.

3	ECTION 11 - TOXICOLOGICAL INFORMATION / CARCINOGENICITY			
ACGIH	Small amount of Silica, crystalline present in Calcium Carbonate & trace residual Formaldehyde present in base emulsion - suspected human carcinogens.			
OSHA	Trace residual Formaldehyde present in base emulsion viewed as a possible cancer hazard.			
IARC	Trace residual Formaldehyde: Human carcinogen.			
NTP	Silica, crystalline, present in small amount in Calcium Carbonate Filler: Known carcinogen. Trace residual Formaldehyde: Anticipated carcinogen.			
DATA WITH POSSIBLE RELEVANCE TO HUMANS	Product contains trace amounts of residual Formaldehyde. OSHA & NTP identify Formaldehyde as a potential carcinogen. IARC identifies Formaldehyde as a human carcinogen. Formaldehyde has been shown to cause mutations in a variety of in-vitro test systems, w/ human significance unknown. Rats have shown carcinogenic effects in respiratory system. Risk should be minimal when used w/ adequate ventilation. Maintain adequate ventilation to prevent exposure above OSHA exposure limits.			
	SECTION 12 - ECOLOGICAL INFORMATION			
AQUATIC TOXICITY	Not known or expected under normal use.			
	SECTION 13 - DISPOSAL CONSIDERATIONS			
WASTE DISPOSAL EPA WASTE CODE IF	Dispose of material in accordance w/ Federal, State & Local regulations.  None.			

## SECTION 15 - REGULATORY INFORMATION

**SECTION 14 - TRANSPORT INFORMATION** 

transportation &/or to non-domestic destinations. PRODUCT NOT REGULATED BY DOT.

Shipping information applicable for domestic ground transport only. Different categorization may be necessary if shipped via other modes of

SPECIAL SHIPPING

INFORMATION

CERCLA – SARA HAZARD CATEGORY	Immediate health hazard; chronic health hazard.	U.S. STATE REGS	See Section 16.
SARA 313	None.	TSCA	All ingredients either on TSCA Inventory or exempt.

## SECTION 16 - OTHER INFORMATION / SPECIAL PRECAUTIONS / LEGEND

NJ Right-to-Know: (Top 5 Ingredients): Calcium Carbonate (1317-65-3), Base Acrylic Emulsion (mixture), Benzoate Ester (proprietary), Water (7732-18-5), Propylene Glycol (57-55-6). Pennsylvania Right-to-Know (Non-Haz @ >3%): Water (7732-18-5). HMIS Ratings: Health: 1, Flammability: 0. Reactivity: 0, Personal Protection: B. WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. (Trace Residual Formaldehyde (50-00-0) in base polymer & Silica, crystalline (14808-60-7) present @ very low levels in calcium carbonate filler.) INTERNATIONAL EMERGENCY NUMBER: 352-323-3500 - INFOTRAC

LEGEND: NA – Not Applicable, NE – Not Established, UN – Unavailable, VOC – Volatile Organic Compound, PEL – Permissible Exposure Limit, TLV – Threshold Limit Value, STEL – Short Term Exposure Limit, MSDS – Material Safety Data Sheet, ACGIH – American Conference of Governmental Industrial Hygienists, SARA – Superfund Amendments & Reauthorization Act of 1986, OSHA – Occupational Safety & Health Administration, HMIS – Hazardous Materials Identification System, NTP – National Toxicology Program, CEIL – Ceiling Exposure Limit, CASRN (CAS Number) – Chemical Abstracts Service Registry Number, TSCA – Toxic Substances Control Act

 Reviewed By:
 Larry G. Brandon
 VP Technology & General Manager
 March 1, 2012

 NAME
 TITLE
 DATE

The information contained herein has been developed based upon currently available scientific data. New information may be developed from time to time which may render the conclusions of this report obsolete. Therefore, no warranty is extended as to the applicability of this information to the user's intended purpose or for the consequences of its use or misuse.